

Crown Marine Batteries.

Built to Leave All Others in Their Wake.

• **Cold Forged Marine Terminal**
Dual threaded stainless steel and cold forged SAE terminals resist corrosion.

• **Low Maintenance Pod Vent**
For periodic evaluation and seasonal maintenance.

• **Tough Connectors**
Thicker, TTP, COS and Post connectors for premium performance and reliability.


• **Posi-Wrap™ Envelope Separators**
Post-Wrap™ separators prevent failure due to short-circuiting and plate shredding.

• **Powerhouse Plate Construction**
Framed centerline lug plate design with LifePlus™ paste for superior performance and longer life.

Battery Specifications

BCI Group	Model Description	Item Number	20 Hr Amp Hour	Electrical Capacity			Inches			Millimeters			Product Footnotes
				MCA Rating	CCA Rating	RC Minutes	L	W	H	L	W	H	
12 VOLT MARINE STARTING BATTERIES													
24	MAR-1000	SM24800	---	1000	800	120 / 25A	10.88	6.75	9.38	276	171	238	DIJM
	MAR-800	SM24650	---	810	650	105 / 25A	10.88	6.75	9.38	276	171	238	DIJM
	MAR-600	SM24500	---	625	500	75 / 25A	10.88	6.75	9.38	276	171	238	DIJM
	MAR-500	SM24440	---	550	440	65 / 25A	10.88	6.75	9.38	276	171	238	DIJM
27	MAR-1000X	SM27800	---	1000	800	125 / 25A	12.63	6.75	9.38	321	171	238	DIJM
12 VOLT MARINE DUAL PURPOSE BATTERIES													
24	24DP550	SM24550	75 Ah	690	550	105 / 25A	10.88	6.75	9.38	276	171	238	DIJMT
27	27DP700	SM27700	100 Ah	875	700	125 / 25A	12.63	6.75	9.38	321	171	238	DIJMT
	27DP600	SM27600	90 Ah	750	600	110 / 25A	12.63	6.75	9.38	321	171	238	DIJMT
31	31DP800	SM31800	105 Ah	1000	800	180 / 25A	13.00	6.75	9.38	330	171	238	DIJMT
12 VOLT MARINE & RV DEEP CYCLE BATTERIES													
24	24T-1000	SM24085	85 Ah	625	500	135 / 25A	10.88	6.75	9.38	276	171	238	DIJL
	24T-800	SM24075	75 Ah	550	440	105 / 25A	10.88	6.75	9.38	276	171	238	DIJL
27	27T-1000	SM27095	95 Ah	845	650	170 / 25A	12.63	6.75	9.38	321	171	238	DIJL
	27T-800	SM27090	90 Ah	625	500	160 / 25A	12.63	6.75	9.38	321	171	238	DIJL
31	31T-1000	SM31105	105 Ah	1000	750	185 / 25A	13.00	6.75	9.38	330	171	238	DIJL

Standard Type



Available with Standard Terminal Style

(BCI Type M Type with Dual SAE / Stainless Threaded Terminals)

Key

D = Standard Terminal (Dual Automotive / Stainless Threaded Terminal)
I = Cover with POD Vent
J = Battery Fitted with Handle or Lifting Lug
L = Antimony Alloy Construction: Low Maintenance Service
M = Calcium Alloy Construction: Maintenance Free Service
T = TightPack Cell Construction

The Power Behind Performance



1445 Majestic Drive | P.O. Box 990
 Fremont, OH 43420-0990 USA
 +1-419-334-7181 | Fax +1-419-334-7124
www.crownbattery.com
sales@crownbattery.com



MAR-800



27T-1000



31DP800



MAR-1000X



31T-1000



MAR-600